



MODEL TD OVERVIEW





Project Number: Project Name: Customer: Date: **Product Information** *Fan:* T Series *Drive:* Direct Drive *Motor(s)* 

FAN SIZE		APPROX. WT.				
	А	В	С	L	н	(lbs.)
24	27-3/16	25 7/8	24	22	7/16	165
30	34 3/16	32 3/8	30	24	7/16	200
36	40 3/16	38 3/8	36	26	7/16	270
42	46 3/16	44 3/8	42	32	7/16	450
48	52 3/16	50 3/8	48	36	7/16	675

## **STANDARD FEATURES**

- Superior Strength Housing: Heavy gauge all-welded housing with steel angle end flange rings.
- Variable Pitch Drives to 7-1/2 HP: Adjustable for systems RPM. Belts sized for 165% driven HP.
- Industrial Duty Motor for Years of Trouble Free-Operation: Totally enclosed fan cooled (TEFC) motor.
- Self-Aligning Pillow Block Bearings

TAGS	QTY	MODEL	HP	RPM	ELECTRICAL	STATIC PRESSURE	AIRFLOW

## **ADDITIONAL OPTIONS**

- Access Door
- Inlet / Outlet Guard
- Companion Flanges

- Special Coatings
- Vibration Isolators
- Mounting Brackets

NOTE: Romla Fans is committed to product improvement and retains the right to change specifications and dimensions at will without prior notification.